

8A2690240600

Opta - Programmable Logic Relay








Technical description:

Opta - Programmable Logic Relay - Expansion Range modules, Analogue modules, 6 outputs, Number of inputs: 6 analog inputs, Option: standard, DC supply version, nominal voltage 24 V, operating from 9.6 to 28.8 V, ambient temperature from -20 to +50 °C

This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-20...50 °C
Commercial description:	OPTA module expansion, analog version with 6 analog (0... 10 V, 4...20 mA, PT 100/1000) inputs, 2 analog (0... 10 V, 4...20 mA) outputs, 4 PWM outputs. Connection to OPTA and to the other modules via the AUX auxiliary port.
Dimensions:	70x84x56.8 mm
Nominal voltage:	24 V
Number of inputs:	6 (programmable up to 8)
Number of outputs:	6 outputs
Operating range dc:	9.6...28.8 V
Programming languages:	Via OPTA main module through ARDUINO IDE or ARDUINO PLC-IDE
Supply:	DC supply version
Certifications and quality approvals (according to type):	    

The information, technical details, data and features contained in this document are subject to change or modification at any time. It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)