

8A5890241600

Opta - Programmable Logic Relay




Technical description:

Opta - Programmable Logic Relay - Expansion Range modules, EMR output modules, 8 poles, 6 A, Number of inputs: 16 digital/analogue inputs, Option: standard, DC supply version, nominal voltage 24 V, operating from 10.6 to 27.5 V, rated power 1 W, ambient temperature from -20 to +50 °C

This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-20...50 °C
Commercial description:	OPTA EMR module expansion Type 8A.58.9.024.1600, digital version. Connection to OPTA via the AUX auxiliary port. Technical features: 16 digital/analog (0...10 V) inputs 8 EMR 6 A outputs Nominal voltage 12...24 V DC
Contact configuration:	8 NO
Dimensions:	70x84x56.8 mm
Nominal voltage:	24 V
Number of inputs:	16
Number of outputs:	8 poles
Operating range dc:	10.6...27.5 V
Programming languages:	ARDUINO IDE or ARDUINO PLC-IDE (IEC 61131-3 languages)
Rated current (contacts):	6 A
Supply:	DC supply version
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time. It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)